

MSP325 HDMI to H.265 Encoder



Key Features

- Support 4K@30Hz, YUV 4:4:4, HDCP 1.X
- Support RTMP/ RTSP /HTTP TS/HTTP FLV/HLS/UDP Multicast /RTP Multicast
- Support importing 4 logos as options in OSD
- Support recording AV to media storage via SD card or USB 3.0
- Manage configuration on Web
- Search and browse vedieo on ONVIF




Specification

Connectors	Input	HDMI	1×HDMI-A
		Audio	1×3.5mm Jack
	Output	H.265	1×RJ45
	Record	USB 3.0	1×USB-A
	Power		1×DC Jack
Performance	Input Resolutions	HDMI	
		SMPTE	720p@23.98/24/25/29.97/30/50/59.94/60 1080i@23.98/24/25/29.97/30/50/59.94/60 1080p@23.98/24/25/29.97/30/50/59.94/60 2160p@30
		VESA	800×600@60 1024×768@60 1280×768@60 1280×1024@60 1366×768@60 1600×1200@60 1920×1080@60 2048×1152@60 2560×1600@60 3840×1080@60 3840×2160@30
	Output Resolutions	H.264 H.265	176×144 240×180 320×180 320×240 320×256 352×228 352×480 400×224 400×320 480×270 480×272 480×320 480×360 480×384 480×480 544×480 608×448 640×360 640×480 704×576 720×404 720×480 720×540 720×576 850×480 1024×576 1280×720 1680×1056 1920×1080 2048×1152 2560×1600 3840×1080 3840×2160@30
	Supported Standard	HDMI	1.4
		H.265	baseline profile/main profile/high profile
Power	Input Voltage	DC 12 1.5A	
Enviroment	Working Temperature	-20 ~60℃	
	Humidity	20 - 90%	
Physical	Weight	Net (Device)	0.3kg
	Dimensions	Net (Device)	90mm×104mm×26mm

Application



Dimension



Order Codes

Product Code	Item
601-0325-01-0	MSP325

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgbink.com
 Headquarter: S601 Weiye Building, Torch Hi-Tech Development Zone, Xiamen, Fujian, P.R.C.

RGBlink

www.rgbink.com



Specifications are correct at time of printing and subject to change or alteration without notice.